

Material Safety Data Sheet

Section I -- Product Identification

Manufacturer: Hottec Inc.
One Terminal Way
Norwich, CT 06360

Phone: (860)887-5111

Product Class: Friction Adhesive
Trade Name : E1210
C.A.S. # : NA

!!Hazard Ratings 0→4
!! Health-2 Fire-3 low-extreme
!! Reactivity -0

Section II -- Hazardous Ingredients

INGREDIENTS	CAS #	%	ACGIH/TLV	OSHA/PEL	mm HG
Methyl Ethyl Ketone	78-93-3	40.	200 ppm	200 ppm	70.6
		STEL=	300 ppm	300 ppm	
Elastomer	9003-18-3	15.			N/AP
Phenol (skin)	108-95-2	<5.	5 ppm	5 ppm	N/AP
Carbon Black •	1333-86-4	5.	3.5 mg/M3	3.5 mg/M3	0
Ortho-Cresol (skin)	95-48-7	<1.	5 ppm	5 ppm	N/AV
Isopropyl Alcohol	67-63-0	15.	400 ppm	400 ppm	33
		STEL=	500 ppm	500 ppm	
Formaldehyde ⊗	50-00-0	<1.	0.3 ppm	0.75 ppm	0
		STEL=	0.3 ppm	2 ppm	
Phenolic Resin	9039-25-2	20.			0

•IARC LISTED AS 2B CARCINOGEN: POSSIBLY CARCINOGENIC TO HUMANS.

⊗LISTED BY IARC AS PROBABLY CARCINOGENIC TO HUMANS
LISTED BY NTP AS REASONABLY ANTICIPATED TO BE
CARCINOGENIC
LISTED BY OSHA AS A CARCINOGEN

***All ingredients in this product are listed in the T.S.C.A. inventory.

Section III -- Physical Data

Boiling Range: 175-180°F

Vapor Density: Heavier than Air

Evap. Rate : Faster than

n-butyl acetate

Liquid Density: Lighter than water

Volatiles vol %65 wgt %56

Wgt per gallon: 7.99 Pounds

Spec. Gravity : 0.95918

Appearance: THICK BLACK LIQUID SHARP ODOR

V.O.C.: 535 G/L

Section IV -- Fire and Explosion Hazard Data

Flammability Class: 1B Flash Point: 20 F TCC LEL: 2.00% UEL: 12.70%

-Extinguishing Media:

Water Fog, Carbon Dioxide, Foam, Dry Chemical.

-Special Firefighting Procedures:

Do not enter confined fire space without proper protective equipment including NIOSH approved self contained breathing apparatus.

-Unusual Fire & Explosion Hazards:

Vapors may build up in poorly ventilated areas and be ignited, causing flash fires or explosions. Vapors are heavier than air and may travel along ground or floor to source of ignition, causing flash fires or explosions.

Section V -- Health Hazard Data

-Permissible Exposure Level:

See Section II

-Effects of Overexposure:

Inhalation: Nose and throat irritation, headache, nausea, loss of Coordination, dizziness, unconsciousness, and even Asphyxiation.

Skin Contact : May cause defatting or dermatitis

Eye Contact : May cause irritation or corneal clouding.

Ingestion : Aspiration into lungs may cause chemical pneumonitis

Chronic Effects: May include kidney and liver damage and dermatitis.

NOTICE: Reports have associated repeated and prolonged occupational over-exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Embryo/fetotoxic effects have been observed in laboratory rats exposed to over 1000 ppm Methyl Ethyl Ketone for most of gestation period.

-Medical Conditions Aggravated by Exposure: None known.

-First Aide:

Inhalation : Remove to fresh air, if not breathing give mouth to mouth, if Breathing difficulty give oxygen, call a physician at once.

Skin Contact: Remove contaminated clothing and launder before reuse. Wash Affected area with plenty of soap and water.

Eye Contact : Flush with plenty of water for at least 15 min (hold eye lids Open) longer if there is indication of residual material in eye.

Ingestion : Do not induce vomiting. Call a physician immediately.

*Never give anything by mouth to an unconscious person.

Section VI -- Reactivity Data

Stability [] unstable [x]stable

Hazardous Polymerization [] may occur [x]will not occur

-Incompatibility: Strong oxidizing agents.

-Conditions to Avoid: See above

-Hazardous Decomposition Products: Carbon dioxide, carbon monoxide, smoke, aliphatics, and others.

Section VII -- Spill or Leak Procedures

-Steps to be taken in case material is released or spilled:

Eliminate all ignition sources, provide adequate ventilation, avoid breathing Vapors, avoid eye and skin contact. Wipe up with rags, paper or other absorbent Materials. Place in suitable closed containers for disposal.

-Waste Disposal Method:

This material if discarded is hazardous and must be properly stored, transported, Disposed of in accordance with applicable local, state, and federal regulations.

Section VIII -- Special Protection Information

-Respiratory Protection:

For air contaminants above TLV or permissible limits use NIOSH approved Respirator for organic vapors.

-Ventilation:

Local exhaust to keep vapors below TLV or permissible limits.

-Protective Gloves:

Impervious

-Eye Protection:

Chemical Goggles

-Other Protective Equipment:

Eye wash and safety shower near by

Section IX -- Special Precautions

-Precautions to be taken in handling and storing:

Use only in a well ventilated area. Eliminate all sources of ignition such As sparks, flames, and non-explosion proof devices. Avoid prolonged or Repeated skin contact or breathing of vapors. For industrial use only, keep Out of the reach of children. Store in tightly closed containers, in a cool dry place Away from all sources of ignition and heat. Large containers should be grounded And interconnected to prevent static build up during transfer operations. Empty Containers of this material may be hazardous since they may contain residual Liquid, vapors or dust. Occupational safety and health specialist to insure that The handling procedures will be adequate and in compliance with applicable laws And regulations.

-Disclaimer of Liability:

The information contained herein is based on data taken from sources believed To be both current and reliable at the time of publication. Hottec Inc. however Makes no warranties express or implied as to its accuracy and assumes no Liability arising from its use by others. Compliance with all applicable federal, State and local laws and regulations remains the responsibility of the users.

Section X -- Additional Regulatory Information

-Sara Title II Section 313:

This product contains the following toxic chemicals subject to the reporting Requirements of section 313 of the Emergency Planning and Community Right To Know Act of 1986 and of 40 CFR 372:

CAS #	Chemical Name	Percent by Weight
78-93-3	Methyl Ethyl Ketone	<50.
108-95-2	Phenol (skin)	1.93
95-48-7	Ortho-Cresol (skin)	<1.
50-00-0	Formaldehyde	<1.

-Prop 65 (CARCINOGEN):

WARNING: This product contains a chemical known to the state of California
To cause Cancer.

CAS # 50-00-0 CHEMICAL NAME- Formaldehyde
Product may contain trace amounts of California Proposition 65 listed chemicals

-PROP 65 (TERATOGEN):

WARNING: This product contains a chemical known to the state of California
To cause birth defects or other reproductive harm.

CAS # - CHEMICAL NAME – None

-PROP 65 (BOTH CARCINOGEN AND TERATOGEN):

WARNING: This product may contain a chemical known to the state of
California to cause cancer or birth defects or other re-
Productive harm.

CAS# - CHEMICAL NAME - None